

High-quality IP Phone at Affordable Price

- TI Chipset, Codec License Included
- HD Voice, Multi-language, 132*64 LCD
- SMS, Voicemail, PoE Optional
- IP PBX System Integration



Yealink SIP-T10T is the ideal standard IP phone for any business or home users. Equipped with powerful TI chipset and VoIP voice engine, it ensures the excellent voice clarity and delivery, meanwhile it is fully interoperable with the majority IP Telephony platforms in the market today. Combined with sleek design, simplified deployment and application, powerful features and flexibility, it offers an unrivalled cost-effective VoIP solution to meet the every-day internet telephony services demand.

Network Features

SIP v1(RFC2543), v2(RFC3261)
NAT transverse: STUN mode
IP Assignment: Static/DHCP/PPPoE
In-Band DTMF, Out-of-Band DTMF, SIP Info
Proxy mode and Peer-to-peer SIP link mode
TFTP/DHCP/PPPoE client
Telnet/HTTP server
DNS client
NAT/DHCP server
Support VLAN, QoS
PoE optional

Voice Features

Wideband Codec: G.722, voice spectrum between 50-7000Hz
Narrowband Codecs: G.711, G.726, G.723.1/iLBC, G.729AB and GSM
VAD, CNG, AEC, PLC, AJB, AGC
Full-duplex hands-free speakerphone

Telephony Features

Call Hold, Call Waiting, Call Transfer, Call Forward
Caller ID, Call List, DND, Redial, Flash
3-way Conference, Speed Dial
MP3 Ring Tone Selectio
Volume Adjustment, Mute, Speakerphone

IP PBX System Integration

SMS, Voicemail, Dial Plan, Dial-now
Remote/Local enterprise phonebook
Call Park, Call Pickup, Distinctive Ringtone
Auto-answer, intercom, Paging

Config, Upgrade and Usage

Language Customization Support
Firmware Upgrade: TFTP/Console/Auto-provision
Auto-provision: TR069 Optional
Direct IP call without SIP proxy
Dial number via SIP server
Dial URL via SIP server

Security

Secure RTP
Digest authentication using MD5/MD5-sess
Secure configuration file via AES encryption

Physical Features

TI Titan Chipset
LCD: blue backlit 132x64
24 keys, 2 indication LEDs
Network Interface: 2xRJ45 10/100M ports
Dimension: 280 x 215 x 90MM
Net Weight: 1.3 kg
Gross Weight: 1.5kg
Power adapter: Input: AC 100~240V
Output: DC 5V/1A
Operating humidity: 10~95%
Storage temperature: up to 60°C

Package Features

Qty/CTN: 5 PCS
N.W/CTN: 6.22 kg
G.W/CTN: 7.02 kg
Measurement: 0.033CMB
Carton Meas: 470 x 287 x 222MM

Certifications

